



GreenShield Inquiry Form

sales@basetek.com or 877-712-BASE (2273)



Company Quote to: _____

Project Reference _____

Contact _____

Equipment/Tag # _____

E-Mail _____

Phone _____

EQUIPMENT INFORMATION

- Pump Model/Size _____
- Motor Frame _____
- Distance Between Shafts _____
- Other _____
- Other _____
- Drawing provided _____

OVERALL DIMENSIONS

- Length _____
- Width _____
- Height ** _____

**** As measured from bottom of GreenShield to bottom of limiting equipment mounting surface. DO NOT include grout allowance. Check all corners for tightest obstruction. GreenShield carries a tolerance of +/- 0.125"**

Mounting Options (Choose one)

- Grouted
- Surface Mount (anchored with PoxyCove)
- Free Float
- Bury/Below Grade

Insert Material (Choose one)

- 303SS
- 316SS
- C276
- Titanium

Construction

- Solid
- Hollow Core
- Have BaseTek recommend (cost/weight)

Material Spec (choose one)

- Zanite Plus
- Red Novolac
- Other

Drip Pan

- Yes
- No

Mounting Block Options

- Standard Uniblock
- Standard block kit (4 blocks)
- Custom Risers

Grout Kit

- Yes
- No

Installation Kit

- Yes
- No

(enter inches)
Maximum epoxy grout depth

Notes: _____
